

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 6.7

Revision Date 21.03.2023

Print Date 12.03.2024

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : n-Butyl acetate for analysis EMSURE®

Product Number : 1.09652

Catalogue No. : 109652

Brand : Millipore

Index-No. : 607-025-00-1

REACH No. : 01-2119485493-29-XXXX

CAS-No. : 123-86-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis

1.3 Details of the supplier of the safety data sheet

Company : Merck Life Science S.r.l.
Via Monte Rosa 93
I-20149 MILANO

Telephone : +39 02 3341 7340

Fax : +39 02 3801 0737

E-mail address : serviziotecnico@merckgroup.com

1.4 Emergency telephone

Emergency Phone # : 800-789-767 (CHEMTREC Italia)
+39-02-4555-7031 (CHEMTREC chiamate internazionali)
+39 02-6610-1029 (Centro Antiveleni Niguarda Ca' Granda - Milano)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 3), H226

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal Word	Warning
Hazard statement(s)	
H226	Flammable liquid and vapor.
H336	May cause drowsiness or dizziness.
Precautionary statement(s)	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
Supplemental Hazard information (EU)	
EUH066	Repeated exposure may cause skin dryness or cracking.

Reduced Labeling (<= 125 ml)

Pictogram



Signal Word	Warning
Hazard statement(s)	none
Precautionary statement(s)	none
Supplemental Hazard information (EU)	
EUH066	Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C ₆ H ₁₂ O ₂
Molecular weight	: 116,16 g/mol
CAS-No.	: 123-86-4
EC-No.	: 204-658-1
Index-No.	: 607-025-00-1

Component	Classification	Concentration
n-Butylacetate		
CAS-No.	123-86-4	Flam. Liq. 3; STOT SE 3; H226, H336
EC-No.	204-658-1	
Index-No.	607-025-00-1	
		<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.



SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.



For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Worker DNEL, acute	inhalation	Local effects	600 mg/m ³
Worker DNEL, acute	inhalation	Systemic effects	600 mg/m ³
Worker DNEL, longterm	inhalation	Local effects	300 mg/m ³
Worker DNEL, longterm	inhalation	Systemic effects	300 mg/m ³



Consumer DNEL, acute	inhalation	Local effects	300 mg/m ³
Consumer DNEL, acute	inhalation	Systemic effects	300 mg/m ³
Consumer DNEL, longterm	inhalation	Local effects	35,7 mg/m ³
Consumer DNEL, longterm	inhalation	Systemic effects	35,7 mg/m ³

Predicted No Effect Concentration (PNEC)

Compartment	Value
Fresh water	0,18 mg/l
Fresh water sediment	0,981 mg/kg
Sea water	0,018 mg/l
Sea sediment	0,0981 mg/kg
Aquatic intermittent release	0,36 mg/l
Sewage treatment plant	35,6 mg/l
Soil	0,0903 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,4 mm

Break through time: 30 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---|--|
| a) Physical state | liquid |
| b) Color | colorless |
| c) Odor | fruity |
| d) Melting point/freezing point | Melting point/range: -78 °C |
| e) Initial boiling point and boiling range | 126,2 °C at 1.013 hPa - OECD Test Guideline 103 |
| f) Flammability (solid, gas) | No data available |
| g) Upper/lower flammability or explosive limits | Upper explosion limit: 7,6 %(V)
Lower explosion limit: 1,7 %(V) |
| h) Flash point | 27 °C - closed cup - Regulation (EC) No. 440/2008, Annex, A.9 |
| i) Autoignition temperature | 415 °C
at 1.010 hPa - DIN 51794 |
| j) Decomposition temperature | No data available |
| k) pH | 6,2 at 5,3 g/l at 20 °C |
| l) Viscosity | Viscosity, kinematic: 0,83 mm ² /s at 20 °C - ASTM D 4450,66 mm ² /s at 40 °C - ASTM D 445

Viscosity, dynamic: 0,73 mPa.s at 20 °C - ASTM D 4450,563 mPa.s at 40 °C |
| m) Water solubility | 5,3 g/l at 20 °C - OECD Test Guideline 105- soluble |
| n) Partition coefficient: n-octanol/water | log Pow: 2,3 at 25 °C - OECD Test Guideline 117 - Bioaccumulation is not expected. |
| o) Vapor pressure | 11,2 hPa at 20 °C - Regulation (EC) No. 440/2008, Annex, A.4 |
| p) Density | 0,88 g/cm ³ at 20 °C - DIN 51757 |
| Relative density | No data available |
| q) Relative vapor density | No data available |
| r) Particle characteristics | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | none |

9.2 Other safety information

- | | |
|-----------------|----------------------------|
| Conductivity | < 0,2 µS/cm |
| Surface tension | 61,3 mN/m at 1g/l at 20 °C |



Relative vapor density 4,01 - (Air = 1.0)
- OECD Test Guideline 115

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

Strong oxidizing agents, Strong reducing agents, Strong bases

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - female - 10.760 mg/kg
(OECD Test Guideline 423)

Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis.

Inhalation: No data available

LD50 Dermal - Rabbit - male and female - 14.112 mg/kg
(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h
(OECD Test Guideline 404)

Remarks: Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation
(OECD Test Guideline 405)

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative



Test Type: Micronucleus test
Species: Mouse
Cell type: Red blood cells (erythrocytes)
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Repeated dose toxicity - Rat - male and female - Oral - 13 Weeks - NOAEL (No observed adverse effect level) - 125 mg/kg - LOAEL (Lowest observed adverse effect level) - 500 mg/kg

Drowsiness

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption of large quantities:

somnolence

Drowsiness

narcosis

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish

flow-through test LC50 - Pimephales promelas (fathead minnow) - 18 mg/l - 96 h



	(OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 44 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	static test ErC50 - Pseudokirchneriella subcapitata (green algae) - 397 mg/l - 72 h (OECD Test Guideline 201) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: Isobutyl acetate
Toxicity to bacteria	static test IC50 - Tetrahymena pyriformis - 356 mg/l - 40 h Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	semi-static test EC50 - Daphnia magna (Water flea) - 34,2 mg/l - 21 d (OECD Test Guideline 211) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: Isobutyl acetate

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 28 d Result: 83 % - Readily biodegradable. (OECD Test Guideline 301D)
Theoretical oxygen demand	2.207 mg/g Remarks: (Lit.)
Ratio BOD/ThBOD	7 - 46 % Remarks: (Lit.)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Discharge into the environment must be avoided.



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1123

IMDG: 1123

IATA: 1123

14.2 UN proper shipping name

ADR/RID: BUTYL ACETATES

IMDG: BUTYL ACETATES

IATA: Butyl acetates

14.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3

14.4 Packaging group

ADR/RID: III

IMDG: III

IATA: III

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

Tunnel restriction code : (D/E)

Further information : No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

National legislation

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : FLAMMABLE LIQUIDS

Other regulations

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.



EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapor.
H336	May cause drowsiness or dizziness.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the



information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

